

GOUDEY

Stain · Lacquer · Finishing Supplies | 1943



goudey.ca

Paint & Varnish Remover

PRODUCT CODES

770

SIZES

4L, 20L



Goudey's 770 is a viscose liquid with a chlorinated solvent designed to lift multiple layers from metal and wood substrates very quickly, many times within the first few minutes. This product is brushable and works great on vertical surfaces.

PRODUCT ADVANTAGES

- Highly effective removal of many common paint coatings
- Slow drying for maximum reaction time
- Clings to vertical, inclined and overhead surfaces
- Ease of stripping

APPROVED COMPANION PRODUCTS	COATING PROPERTIES		DRY TIMES	
788 Lacquer Reducer	Specific Gravity	1.16 gr/cm ³	Swell Time	10-15 mins
706 Toluene	VOC (coating)	230 g/l		
707 Xylene	VOC (material)	740 g/l		
700 Methyl Hydrate	Shelf Life	24 months		
	Storage	Must be kept away from heat or sparks		

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

No special treatment or cleaning is required when the intended use is for removing and stripping.

MIXING

This product requires no mixing, use straight out of the container.

APPLICATION

The customer is responsible for following the recommended application procedures. Failure to do so will likely result in unsatisfactory product performance. Always test the complete coating system **prior** to the start up of production. A patch test is recommended on an area not normally visible.

1. Safety

To avoid contact with skin and eyes, wear chemical resistant gloves and use a fresh air respirator.

2. Application

- Apply by brush.
- Allow 10 to 15 minutes to penetrate and lift old finishes.
- Remove old finishes with a scraper or putty knife
- Repeat procedure if necessary
- Brush with a stiff bristle-brush to remove paint residues.
- Clean surface with Goudey 788 lacquer reducer. If fish eye is a problem, clean the surface with 700, 706 or 707
- For hard to strip finishes (e.g. post catalyzed topcoats), rough the surface with 80 grit sandpaper before applying stripper.

Note: Goudey 770 is NOT recommended to use over fiber glass or plastic.

3. New finish preparation

Make sure there is NO residue of old finishes on entire surfaces.

PRECAUTIONS

Equipment

Goudey 770 is applied by brush.

Containers

Goudey 770 Paint & Varnish Remover should be stored in the original container or in a metal container with a secure lid.

DISCLAIMER These products are designed **for industrial use only**. Goudey views safety as a top priority. Please refer to the Safety Data Sheet for information on the safe use of this product. Values shown are calculated estimates and should not be construed as product specifications. We cannot anticipate all conditions under which this information and our products or the products of other manufacturers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, we sell the products without warranty, and users assume all responsibility and liability for loss or damage arising from the use of our products whether used alone or a combination with other products. Use of unapproved or reclaimed solvent blends may reduce film properties and is not recommended.