



PROPOLY - Interior WATER-BASED POLYURETHANE

PRODUCT CODES

- PPINT10 (FLAT)
- PPINT30 (SATIN)
- PPINT50 (SEMI-GLOSS)
- PPINT90 (GLOSS)

SIZES

4 L

Goudey **PROPOLY** Interior is a professional grade non-yellowing water-based polyurethane. Goudey **PROPOLY** Interior is ideal for commercial and residential flooring and furniture that requires exceptional protection. Goudey **PROPOLY** Interior is easy to apply, dries quickly and is low in odour.

PRODUCT ADVANTAGES

- **Excellent for floors**
- **Ideal for all interior wood surfaces**
- **Dries clear**
- **Low odour and Low VOC**
- **Easy soap and water clean-up**

APPROVED COMPANION PRODUCTS	COATING PROPERTIES		DRY TIMES
W Series Wiping Stains	Viscosity (Ford Cup #4)	34-36 seconds	1-2 hours at 21°C at 50% relative humidity. Drying time may vary based on temperature and relative humidity.
WB Series Water-Based Wiping Stains	Solids Content (wt.)	30%	
D Series Non Grian Raising Stains	Solids Content (volume)	27%	
	Theoretical Coverage	Up to 700 sq. ft/gal	
	Specific Gravity	1.03-1.05 kg/L	
	VOC (coating)	215 g/L	
	Shelf Life	12 months in a well sealed container	
	Storage	Minimum temperature at 5°C to a maximum of 35°C. Freeze-thaw stable. Let completely thaw before using. KEEP OUT OF REACH OF CHILDREN.	

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Unfinished floors:

- Sand according to NWFA recommendations using 120 or 150 grit sandpaper.
- Do not use steel wool. Vacuum thoroughly and wipe with a dry cloth to remove all sanding dust before applying stain and/or Goudey PROPOLY.

Stained floors:

- Follow the stain manufacturer's application directions and test with Goudey PROPOLY for compatibility.

Re-coating floors:

- Clean floor to remove all dirt and sand with a 120 grit sandpaper to roughen up the top coat. Vacuum thoroughly and wipe with a dry cloth to remove all sanding dust before applying a new coat of Goudey PROPOLY.

APPLICATION

Recommended Conditions for Application

- Wood humidity level: 30-80%
- Temperature: Allow product to reach room temperature, 15° – 25° C (59° -77° F)

Application

1. Stir well and let it sit for 5-10 minutes before applying it, allowing the air bubbles to escape.
2. Test for compatibility between existing product and finish first. If the test fails, sand down to bare wood before the application of the finish.
3. Apply uniform coats following the wood grain with lamb's wool, high quality brush, lint free 6mm roller, weighted applicator or spray gun. If required, thin with water. Work gently with the applicator to minimize the amount of air mixed into the finish.
4. Allow 1-3 hours to dry and lightly sand with 220 grit sandpaper between coats.
5. Repeat for 2 to 3 coats.
6. Allow 24 hours dry time for light foot traffic. Allow 7 days for heavy traffic and furniture.

PRECAUTIONS

Clean-up: Clean all tools with warm water and soap immediately after use.

Storage: Keep in dry area.

KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER These products are designed **for industrial use only**. Goudey views safety as a top priority. Please refer to the Safety Data Sheet for information on the safe use of this product. Values shown are calculated estimates and should not be construed as product specifications. We cannot anticipate all conditions under which this information and our products or the products of other manufacturers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, we sell the products without warranty, and users assume all responsibility and liability for loss or damage arising from the use of our products whether used alone or a combination with other products. Use of unapproved or reclaimed solvent blends may reduce film properties and is not recommended.